

SPEEDMASTER™

BI-FOLDING TRACKLESS SPEED GATES



- A** Catch plate for security
- B** Safety edges as standard
- C** Heavy duty hinges
- D** Infill options vertical bar or any CLD system

Conforms to **BS EN 12453**



FEATURES

- Very cost effective
- Integrates with other security products
- No keyed locks

SUITABLE FOR

- Sensitive security areas
- Government sites
- Power and utility sites



DESCRIPTION

To maintain the protection of their perimeter, high level security premises need gates that open and close quickly. The SpeedMaster™ bi-folding trackless speed gates open more than twice the speed of traditional swinging gates.

The rapid opening and closing action ensures traffic rarely stands still, so there's less opportunity for tailgating. With the SpeedMaster™ gates folding in on each other as they open, they're ideal where space is at a premium.

Security is high on the agenda too, with the RHS steel frame gates featuring either tubular steel vertical bars, or your choice of infill, including our ultra-defensive Securus™ range. You can also fit spiked tops, warning lights and sirens if needed.

Designed for continuous operation, SpeedMaster™ gates use a PLC-controlled motor, worm and wheel gearbox with a direct-drive shaft connected to the leaf gate, so they open and close effortlessly smoothly. They're also compatible with most access control options, including keypad, proximity card and, remote control.

FINISH

Zinc plated and polyester powder coated.

DIMENSIONS

| | |
|---------------|--------------|
| Height | Up to 4000mm |
| Width | Up to 9000mm |

All dimensions are nominal

