



INTERNAL VIEW

DESCRIPTION

When you have a high security perimeter, you need a security gate system to complement this, offering equal protection for access control. The LockMaster S2 Auto™ System is the next generation in Security Automated Swing Gates. Available in double leaf, it consists of two layers of Securus mesh with the automation fitted on the inside of the compound, providing a plentiful protection for the likes of Government projects, data centres, airports and high security units.

The LockMaster S2 Auto™ System is a great cost effective way to upgrade your site to automated access control. Security features include anti-lift-off hinges providing maximum security for the most high security units.

Carrying certification to LPS 1175 Issue 8 - B3 (SR2), LockMaster S2 Auto™ will withstand heightened threats and attacks from mechanical tools.

FINISH

Hot dip galvanised and polyester-powder coated. Available in a range of RAL colours.

FEATURES

- Large range of heights & widths available
- LPS 1175 Issue 8 - B3 (SR2) security rating
- Double layer of Securus mesh infill
- Any RAL colour available
- High performance rated access control

SUITABLE FOR

- Government buildings
- Data Centres
- Airports
- Utility suppliers
- High secure units



INTERNAL VIEW



EXTERNAL VIEW

DIMENSIONS

Height	2.4m to 5m
Width (double)	2.4m to 10m
Post size (double)	Minimum of 150 x 150mm but will increase in size depending on width of gate

All dimensions are nominal



LOCKMASTER S2 AUTO

The LockMaster S2 Auto™ posts are manufactured with base plates and size of posts will be determined by the width of gates ordered. Posts are flanged to accept any of the CLD Systems. Securus SR rated mesh is attached to the gate using pin hex security screws and clamps.

LOCKING ARRANGEMENTS

All LockMaster S2 Auto™ Gates have a purpose made lock box with a slide-bar to enable the gates to be deadlocked, should the automation system need to be powered down.

Going the **extra secure mile... worldwide**



Distributors in:

Australia | Estonia | France | Italy | New Zealand | Scotland | South Africa | Sweden | UAE | UK | USA



Head office:

Unit 11, Springvale Business Centre,
Millbuck Way, Sandbach, Cheshire, CW11 3HY

Tel +44 (0)1270 764751

Fax +44 (0)1270 757503

Email info@cld-fencing.com

www.cld-fencing.com

London Office:

47 Gee Street, London, EC1V 3RS

Tel +44 (0)1270 764751

Sydney Office:

6th Floor, 10 Herb Elliot Avenue, Sydney Olympic Park, New South Wales 2127

Tel +61 (0) 2 8310 7429

Dubai Office:

Office 508, 5th Floor, Fairmont, Sheikh Zayed Road, Dubai, UAE

Tel +971 (0) 4311 6717

All information contained within this document including technical details, graphics and photographs are copyright © CLD Fencing Systems LLP 2016.

This document may not be reproduced, copied, transmitted or stored in any form without written permission from CLD Fencing Systems.

All information correct at time of printing. We reserve the right to alter specification without notice.