



DESCRIPTION

CLD Fencing Systems LockMaster S1 Dulok-25 Swing Gates are the newest advancements in our S Range of Swing Gates. Available in 4 different mesh options, including Dulok-25 infill meaning the LockMaster S1 Dulok-25 Swing Gate can blend seamlessly in with your fence line.

The new LockMaster S1 Dulok-25 Swing Gate holds an LPS 1175 Issue 8 security rating giving you a guarantee of 1-minute delay against attack, whilst also being Secured by Design accredited, making them police preferred for specification. The LockMaster S1 Dulok-25 Swing Gates are an affordable level of security with a guaranteed level of delay.

This system is available in double & single leaf with rear or centre hung options with a minimum post size of 80 x 80 mm square hollow sections (SHS). The LockMaster S1 Dulok-25 Swing Gates are a great choice for use on projects such as Schools, Warehouses & Distribution Centres, Industrial and Commercial Sites and Housing Sites.

FINISH

Galvanised and polyester-powder coated. Available in a wide range of RAL colours.

DIMENSIONS

Height	1.8m to 3m
Width (single)	0.5m to 3m
Width (double)	1m to 6m
Post size	80x80mm minimum square hollow section
Gate Frame	50x50x2mm vertical stiles SHS min/ 40x40x2mm horizontal rails SHS min
Dulok-25 Mesh & Wire	200x25mm mesh 6mm verticals 2 x 8mm horizontals



All dimensions are nominal, for further information please contact CLD Fencing Systems. All information is correct at time of production. We reserve the right to alter specification without notice.

FEATURES

- LPS 1175 Issue 8 security rating with guaranteed 60 seconds delay against attack
- 4 different mesh options available
- Full range of RAL colours
- Fully compatible with CLD Fencing Range of security toppings
- A shrouded slide-bar is available as an optional extra to remove any potential foothold



SUITABLE FOR

- Schools
- Warehouses & Distribution Centres
- Industrial & Commercial Sites
- Housing Sites

LOCKMASTER S1 DULOK-25 SWING GATE

The LockMaster S1 Dulok-25 Swing Gate posts are manufactured for ground bury or base plated & size of posts will be determined by the width of gates ordered. Separate angle iron flanges are supplied for on-site installation to accept any of the CLD Systems. Dulok-25 mesh is attached to the gate using CLD Fencing Systems clamp bars, M8 bolts & shear nuts to rear.

LOCKING ARRANGEMENTS

All LockMaster S1 Dulok-25 Swing Gates have a purpose made lock box with a slide-bar to enable the gates to be deadlocked with certified padlock.

Going the **extra secure mile... worldwide**



Distributors in:

Australia | Estonia | France | Italy | New Zealand | Scotland | South Africa | Sweden | UAE | UK | USA



Head office:

Unit 11, Springvale Business Centre,
Millbuck Way, Sandbach, Cheshire, CW11 3HY

Tel +44 (0)1270 764751

Fax +44 (0)1270 757503

Email info@cld-fencing.com

www.cld-fencing.com

London Office:

47 Gee Street, London, EC1V 3RS

Tel +44 (0)1270 764751

Sydney Office:

6th Floor, 10 Herb Elliot Avenue, Sydney Olympic Park, New South Wales 2127

Tel +61 (0) 2 8310 7429

Dubai Office:

Office 508, 5th Floor, Fairmont, Sheikh Zayed Road, Dubai, UAE

Tel +971 (0) 4311 6717

All information contained within this document including technical details, graphics and photographs are copyright © CLD Fencing Systems LLP 2016.

This document may not be reproduced, copied, transmitted or stored in any form without written permission from CLD Fencing Systems.

All information correct at time of printing. We reserve the right to alter specification without notice.